



NULLA

Davide Groppi / 2010

An extreme expression of subtraction, uniting optics and electronics as an answer to the ultimate challenge: the absence of structural support and the essence of light.

Nulla is a project that represents both the beginning and end of our work on light. It's the beginning, in the sense that we have always been looking for absolute light, one coming from a distance, almost without a source. It's the end in that every time we look at Nulla, we feel as though we can't get it better than that.

Nulla generates light and propagates mystery. Nulla is the most generous of our lamps. Its sole objective is to hide and give all the attention to whatever it is lighting. What we see is only a tiny black hole, as if it were drawn on the ceiling.


A circle in the ceiling hiding a very bright LED and lens to project the light.

XXIII Compasso d'Oro ADI Award, 2014

Recessed / Direct / Indoor

Material Metal
Finish .00 Standard

Note Luminaire with Extradark comfort system - NULLA and NULLA 18: visible hole Ø 0.71" - NULLA 25: visible hole Ø 0.98" - NULLA 18 and NULLA 25: luminaire removable for maintenance.




NULLA - BEAM 23°

9W
24V DC
2700K - 304lm / 3000K - 327lm
Beam 23°
CRI >90
UGR <19
Driver not included



Standard - 2700K
Standard - 3000K

1A4100003.27.20
1A4100003.30.20



NULLA - BEAM 32°

9W
24V DC
2700K - 384lm / 3000K - 413lm
Beam 32°
CRI >90
UGR <19
Driver not included



Standard - 2700K
Standard - 3000K

1A2110003.27.20
1A2110003.30.20



NULLA 18 - BEAM 20°

3W
24V DC
2700K - 162lm / 3000K - 173lm
Beam 20°
CRI >90
UGR <19
Driver not included



Standard - 2700K
Standard - 3000K

1A2010003.27.20
1A2010003.30.20

The sizes are expressed in inches.



NULLA 25 - BEAM 23°

6,5W
24V DC
2700K - 228lm / 3000K - 245lm
Beam 23°
CRI >90
UGR <19
Driver not included



Standard - 2700K
Standard - 3000K

1A4080003.27.20
1A4080003.30.20



NULLA 25 - BEAM 32°

6,5W
24V DC
2700K - 288lm / 3000K - 310lm
Beam 32°
CRI >90
UGR <19
Driver not included



Standard - 2700K
Standard - 3000K

1A2020003.27.20
1A2020003.30.20



NULLA 25 T24

5,6W
Max 500mA DC
3000K - 357lm / 2700K - 357lm
CRI >90
Driver not included



Standard - 2700K
Standard - 3000K


1A1010003-27
1A1010003

Compulsory accessories


Installation kit



Plasterboard flange 0.49"				Not included
Matt Black	Cut-out Ø 0.83" - Minimum space for mounting 3.94" - IP65	NULLA	1A2200400.00.00	



Plasterboard flange 0.49"				Not included
	Cut-out Ø 0.87" - Minimum space for mounting 7.48"	NULLA 18	1A2210400.00.00	



Plasterboard flange 0.49"				Not included
Matt Black	Cut-out Ø 1.38" - Minimum space for mounting 7.48"	NULLA 25	1A2170400.00.00	




Plasterboard flange 0.49"				Not included
Matt Black	Cut-out Ø 1.38" - Minimum space for mounting 7.48"	NULLA 25	1A3980400.00.00	




Plasterboard flange 0.49"				Not included
	Cut-out Ø 1.38" - Minimum space for mounting 6.30"	NULLA 25 T24	18250003	


Electrical power supply



Driver LED				Not included
220-240V(100-127V)	24V/20W(15W)/IP20/PUSH	NULLA / NULLA 18 / NULLA 25	1Z0240870.24	



Driver LED				Not included
220-240V(100-127V)	24V/16W(15W)/IP20/DALI	NULLA / NULLA 18 / NULLA 25	1Z0241180.24	



Driver LED				Not included
120-277V	24V/60W/IP20/TRIAC - 1-10V	NULLA / NULLA 18 / NULLA 25	1Z2020040	


The sizes are expressed in inches.

Optional accessories


Installation kit




Trapdoor for plasterboard 0.49"				Not included
Standard	Cut-out 7.87" x 7.87"	NULLA	1A3780000.00.00	



Trapdoor for plasterboard 0.49"				Not included
Standard	Cut-out 15.75" x 15.75"	NULLA	1A3790000.00.00	



Masonry Box				Not included
	Dimensions 7.44" x 17.52"	NULLA 18	1A2390000.00.00	



Masonry Box				Not included
	Dimensions 7.44" x 17.52"	NULLA 25	1A2380000.00.00	



NULLA