

DOT R

Omar Carraglia - Davide Groppi / 2015



A tool to light.

A luminaire designed for use with state-of-the-art LED modules to offer superior performance and a wide range of light beams.

Elemento di luce.


Un apparecchio illuminante progettato per utilizzare moduli a LED in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi.

Recessed / Direct / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Adjustable luminaire - For installation: plasterboard cut-out 40 x 40 mm - Minimum space for mounting 85 mm.

Apparecchio orientabile - Per installazione: dimensioni taglio cartongesso 40 x 40 mm - Spazio minimo per incasso 85 mm.




DOT R

13W
 Max 350mA DC
 2700K / 3000K
 CRI 97
 Driver not included
 CE IP20

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K

1A4770300.27.20
 1A4770300.30.20
 1A4770400.27.20
 1A4770400.30.20



DOT R 51

Max 10W - GU10
 100-240V - 50/60Hz
 Bulb not included
 ON/OFF
 CE IP20

Matt White - ON/OFF
 Matt Black - ON/OFF

1A3700300.00.00
 1A3700400.00.00

The sizes are expressed in millimeters.


Compulsory accessories / Accessori obbligatori

Other accessories / Altri accessori




Lens / Lente	Not included		
Beam - 14°	2700K - CRI 97 - 983lm 3000K - CRI 97 - 1038lm	DOT R	1A3090000.00.00
Beam - 24°	2700K - CRI 97 - 943lm 3000K - CRI 97 - 996lm	DOT R	1A3100000.00.00
Beam - 36°	2700K - CRI 97 - 955lm 3000K - CRI 97 - 1005lm	DOT R	1A3110000.00.00
Beam - 50°	2700K - CRI 97 - 965lm 3000K - CRI 97 - 1016lm	DOT R	1A3120000.00.00


Electrical power supply / Alimentazione elettrica



Driver LED	Not included		
220-240V(100-127V)	350mA/18W(15W)/IP20/PUSH - 1-10V	DOT R	1Z0240870.350



Driver LED	Not included		
220-240V(100-127V)	350mA/17W(15W)/IP20/DALI	DOT R	1Z0241180.350



Driver LED	Not included		
220-240V	350mA/17W/IP20/TRIAC/IGBT	DOT R	1Z0240850.350

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16	Not included		
	220-240V - 5,5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	DOT R 51	1Y0330500




LED SORAA - GU10 - MR16	Not included		
	230V - 7,5W - 10° - 3000K - 410lm - CRI 95 - Energy Efficiency G - Dimmable	DOT R 51	1Y1580010




LED SORAA - GU10 - MR16	Not included		
	230V - 7,5W - 10° - 2700K - 390lm - CRI 95 - Energy Efficiency G - Dimmable	DOT R 51	1Y1580210

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Honeycomb louvre / Porta accessori + Frangiluce nido d'ape		Not included
	DOT R	1X0080400.01.00




Elliptical filter / Filtro ellittico		Not included
Standard	DOT R	1X0080000.02.00




Blue filter / Filtro blu		Not included
Standard	DOT R	1X0080000.03.00




Red filter / Filtro rosso		Not included
Standard	DOT R	1X0080000.04.00




Yellow filter / Filtro giallo		Not included
Standard	DOT R	1X0080000.05.00



Darklight		Not included
MR16	DOT R 51	51580040



25° beam filter / Filtro fascio 25°		Not included
MR16	DOT R 51	51580020



36° beam filter / Filtro fascio 36°		Not included
MR16	DOT R 51	51580030

The sizes are expressed in millimeters.

