

Wall or ceiling lighting system with direct light for indoor use.

Light runs on a wire.
An almost imperceptible wire, suspended in space.
Like a tightrope walker on an ultra-thin wire, the light reaches everywhere, thrilling and impalpable.

The rose is in matt white painted steel.
The tie-rod body is in matt white painted aluminium, the tensioner is in polished chrome galvanised brass.
The luminaire is in textured matt black polyamide.
The lens can be replaced even with the luminaire assembled.

The light source is LED with integrated module.
The unipolar cable is in galvanised steel and silver-copper.
The version with rose (class I) has an integrated driver with dimmer function.
For the version without rose (class III) the driver is not included but available as an accessory.



Finish

.04 Matt Black






Custom finish available on request (tie rods and wall/ceiling driver only).

Remote driver version



Wall/ceiling driver version




OHM SPOT

3,3W
 Max 350mA DC
 2700K / 3000K
 CRI >95
 Driver not included

Matt Black - 2700K	1A3000403.27.20
Matt Black - 3000K	1A3000403.30.20

Compulsory accessories

Installation kits



Tie rods (positive/negative)		Not included
Matt White	2 Pieces	1A3020303.00.00




Unipolar wire - 472.44"		Not included
	Max 60V DC	1A3060000.00.00


Unipolar wire - 944.88"		Not included
	Max 60V DC	1A3070000.00.00

Unipolar wire - 1889.76"		Not included
	Max 60V DC	1A3080000.00.00

Drivers



Driver		Not included
220-240V(100-127V)	350mA/18W(18W)/IP20/DALI - PUSH - 1-10V	1Z0240530.350



Wall/ceiling driver		Not included
Matt White	Input 120V - 60Hz Output 350mA - Max 4x3,3W - IP20 DALI - PUSH - 1-10V	1A3010303.00.07

Compulsory accessories

Other accessories



Lens		Not included	
Beam - 14°	2700K - CRI >95 - 272lm	OHM SPOT	1A3090000.00.00
	3000K - CRI >95 - 288lm		
Beam - 24°	2700K - CRI >95 - 271lm	OHM SPOT	1A3100000.00.00
	3000K - CRI >95 - 286lm		
Beam - 36°	2700K - CRI >95 - 257lm	OHM SPOT	1A3110000.00.00
	3000K - CRI >95 - 273lm		
Beam - 50°	2700K - CRI >95 - 254lm	OHM SPOT	1A3120000.00.00
	3000K - CRI >95 - 270lm		

Optional accessories

Installation kits




Wire guide		Not included	
Matt Black	1 Piece		1X0020400.01.00




Weight kit for suspension version		Not included	
	4 Pieces		1A3050000.00.00






Remote driver version



Wall/ceiling driver version



Suspension version