

191900	STANDARD DIM 1-10 V - PUSH	MAX 700 mA DC - 8 W LED - 3000K - 840 lm FORO VISIBILE Ø 25 mm - APPARECCHIO ESTRAIBILE PER MANUTENZIONE KIT INSTALLAZIONE OBBLIGATORIO NON INCLUSO DRIVER LED INCLUSO INPUT 110-240 V - 50/60 Hz - DIMMERABILE 1-10 V - PUSH VISIBLE HOLE Ø 25 mm - LUMINAIRE REMOVABLE FOR MAINTENANCE COMPULSORY INSTALLATION KIT NOT INCLUDED INCLUDES LED DRIVER INPUT 110-240 V - 50/60 Hz - 1-10 V - PUSH DIMMABLE
191800	STANDARD DIM DALI VERSION	MAX 700 mA DC - 8 W LED - 3000K - 840 lm FORO VISIBILE Ø 25 mm - APPARECCHIO ESTRAIBILE PER MANUTENZIONE KIT INSTALLAZIONE OBBLIGATORIO NON INCLUSO DRIVER LED INCLUSO INPUT 110-240 V - 50/60 Hz - DIMMERABILE DALI VISIBLE HOLE Ø 25 mm - LUMINAIRE REMOVABLE FOR MAINTENANCE COMPULSORY INSTALLATION KIT NOT INCLUDED INCLUDES LED DRIVER INPUT 110-240 V - 50/60 Hz - DALI DIMMABLE

KIT INSTALLAZIONE OBBLIGATORIO / COMPULSORY INSTALLATION KIT



182500	STANDARD	FLANGIA PER CARTONGESSO 12,5 mm DIMENSIONI TAGLIO CARTONGESSO Ø 35 mm SPAZIO MINIMO PER INCASSO 160 mm PLASTERBOARD FLANGE 12,5 mm PLASTERBOARD CUT-OUT Ø 35 mm MINIMUM SPACE FOR MOUNTING 160 mm
--------	----------	--



DESIGN DAVIDE GROPPI - 2015
 LAMPADA DA INCASSO DA SOFFITTO - METALLO
 RECESSED CEILING LAMP - METAL
 ENERGY CLASS: A+

NULLA 25 IP65

CE IP 20/IP 65



192000	STANDARD DIM 1-10 V - PUSH	<p>MAX 700 mA DC - 8 W LED - 3000K - 840 lm FORO VISIBILE Ø 25 mm - APPARECCHIO ESTRAIBILE PER MANUTENZIONE KIT INSTALLAZIONE OBBLIGATORIO NON INCLUSO DRIVER LED INCLUSO INPUT 110-240 V - 50/60 Hz - DIMMERABILE 1-10 V - PUSH VISIBLE HOLE Ø 25 mm - LUMINAIRE REMOVABLE FOR MAINTENANCE COMPULSORY INSTALLATION KIT NOT INCLUDED INCLUDES LED DRIVER INPUT 110-240 V - 50/60 Hz - 1-10 V - PUSH DIMMABLE</p>
190800	STANDARD DIM DALI VERSION	<p>MAX 700 mA DC - 8 W LED - 3000K - 840 lm FORO VISIBILE Ø 25 mm - APPARECCHIO ESTRAIBILE PER MANUTENZIONE KIT INSTALLAZIONE OBBLIGATORIO NON INCLUSO DRIVER LED INCLUSO INPUT 110-240 V - 50/60 Hz - DIMMERABILE DALI VISIBLE HOLE Ø 25 mm - LUMINAIRE REMOVABLE FOR MAINTENANCE COMPULSORY INSTALLATION KIT NOT INCLUDED INCLUDES LED DRIVER INPUT 110-240 V - 50/60 Hz - DALI DIMMABLE</p>

KIT INSTALLAZIONE OBBLIGATORIO / COMPULSORY INSTALLATION KIT

182500	STANDARD	<p>FLANGIA PER CARTONGESSO 12,5 mm DIMENSIONI TAGLIO CARTONGESSO Ø 35 mm SPAZIO MINIMO PER INCASSO 160 mm PLASTERBOARD FLANGE 12,5 mm PLASTERBOARD CUT-OUT Ø 35 mm MINIMUM SPACE FOR MOUNTING 160 mm</p>
--------	----------	---



APPARECCHIO ESTRAIBILE PER MANUTENZIONE
LUMINAIRE REMOVABLE FOR MAINTENANCE

